

Listing of: (memory data)

Channel Group: Corrected Torque and Power Page 1 of 1

Printed on Jul 3, 2012 at 10:24:30

Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr Chp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Airl+2 scfm	AirTmp degF	VolEff %
**	4500	581.4	498.2	211.0	0.473	0.00	0	80	0.0
	4600	588.6	515.5	204.2	0.442	0.00	0	80	0.0
	4700	599.9	536.8	209.4	0.435	0.00	0	79	0.0
	4800	606.0	553.8	223.3	0.449	0.00	0	79	0.0
	4900	613.6	572.5	223.4	0.435	0.00	0	79	0.0
	5000	615.5	585.9	216.2	0.411	0.00	0	79	0.0
	5100	614.7	596.9	212.0	0.396	0.00	0	79	0.0
	5200	616.0	609.9	210.7	0.386	0.00	0	79	0.0
	5300	611.6	617.2	242.0	0.438	0.00	0	80	0.0
	5400	617.3	634.7	223.8	0.394	0.00	0	80	0.0
	5500	613.7	642.7	234.3	0.408	0.00	0	79	0.0
	5600	623.0	664.3	250.8	0.422	0.00	0	79	0.0
	5700	612.6	664.9	240.2	0.404	0.00	0	79	0.0
	5800	610.1	673.8	257.9	0.428	0.00	0	78	0.0
**	5900	593.4	666.6	256.4	0.431	0.00	0	78	0.0
	6000	588.1	671.9	254.5	0.425	0.00	0	79	0.0
	6100	584.1	678.4	268.8	0.445	0.00	0	79	0.0
	6200	584.5	690.0	269.9	0.440	0.00	0	79	0.0
	6300	576.9	692.0	247.4	0.402	0.00	0	79	0.0
	6400	570.0	694.5	262.9	0.427	0.00	0	80	0.0
	6500	556.8	689.0	265.5	0.435	0.00	0	80	0.0
	6600	553.1	695.1	277.4	0.451	0.00	0	80	0.0
	6700	540.7	689.8	304.5	0.500	0.00	0	80	0.0
	6800	543.8	704.0	294.1	0.473	0.00	0	80	0.0
**Range: 4500 RPM - 5900 RPM									
AVG:	5200	607.8	602.2	227.7	0.424	0.00	0	79	0.0
MIN:	4500	581.4	498.2	204.2	0.386	0.00	0	78	0.0
MAX:	5900	623.0	673.8	257.9	0.473	0.00	0	80	0.0