

Listing of: (memory data) 5
 Channel Group: Corrected Torque and Power Page 1 of 1
 Printed on Apr 8, 2009 at 15:25:25
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Air1+2 scfm	AirTmp degF	VolEff %
**	3900	596.2	442.8	184.6	0.450	0.00	0	59	0.0
	4000	595.9	453.8	181.8	0.433	0.00	0	59	0.0
	4100	608.0	474.6	187.9	0.428	0.00	0	59	0.0
	4200	621.2	496.8	184.6	0.402	0.00	0	59	0.0
	4300	629.7	515.5	193.8	0.406	0.00	0	59	0.0
	4400	637.1	533.7	191.1	0.387	0.00	0	59	0.0
	4500	635.1	544.2	209.9	0.417	0.00	0	59	0.0
	4600	636.3	557.3	225.4	0.437	0.00	0	59	0.0
	4700	630.8	564.5	224.5	0.430	0.00	0	59	0.0
	4800	631.1	576.7	228.8	0.429	0.00	0	59	0.0
	4900	624.5	582.6	220.1	0.409	0.00	0	59	0.0
	5000	620.0	590.2	226.3	0.415	0.00	0	59	0.0
	5100	617.9	600.0	237.3	0.428	0.00	0	59	0.0
	5200	611.5	605.4	233.1	0.418	0.00	0	60	0.0
	5300	605.5	611.1	237.5	0.422	0.00	0	60	0.0
	5400	599.0	615.8	247.9	0.437	0.00	0	60	0.0
	5500	587.8	615.6	251.1	0.443	0.00	0	60	0.0
**	5600	575.1	613.2	276.6	0.491	0.00	0	60	0.0
	5700	569.1	617.7	585.1	1.032	0.00	0	60	0.0
	5800	560.6	619.0	696.9	1.227	0.00	0	60	0.0
	5900	539.5	606.1	686.0	1.235	0.00	0	60	0.0
	6000	518.4	592.2	700.3	1.293	0.00	0	60	0.0
	6100	486.4	565.0	688.0	1.334	0.00	0	60	0.0

**Range: 3900 RPM - 5600 RPM
 AVG: 4750 614.6 555.2 219.0 0.427 0.00 0 59 0.0
 MIN: 3900 575.1 442.8 181.8 0.387 0.00 0 59 0.0
 MAX: 5600 637.1 615.8 276.6 0.491 0.00 0 60 0.0

607.4
575.8