

Listing of: (memory data)

Channel Group: Corrected Torque and Power Page 1 of 1

Printed on Feb 2, 2005 at 16:30:37

Test Description: Accel. Test - 300 rpm/second

16.1 Vacuum

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Air1+2 scfm	AirTmp degF	VolEff %
	3500	491.1	327.3	132.7	0.423	0.00	0	57	0.0
**	3600	489.6	335.6	133.9	0.415	0.00	0	56	0.0
	3700	510.9	359.9	130.7	0.378	0.00	0	56	0.0
	3800	533.2	385.8	138.0	0.372	0.00	0	56	0.0
	3900	550.0	408.4	149.3	0.380	0.00	0	56	0.0
	4000	550.5	419.3	155.7	0.387	0.00	0	56	0.0
	4100	553.1	431.8	157.0	0.378	0.00	0	56	0.0
-	4200	553.2	442.4	148.6	0.350	0.00	0	56	0.0
	4300	546.7	447.6	157.7	0.367	0.00	0	56	0.0
	4400	547.2	458.5	162.4	0.369	0.00	0	56	0.0
	4500	540.7	463.3	166.4	0.374	0.00	0	55	0.0
	4600	535.8	469.3	176.0	0.391	0.00	0	56	0.0
	4700	526.3	471.0	188.8	0.416	0.00	0	52	0.0
	4800	518.9	474.2	179.4	0.393	0.00	0	53	0.0
	4900	500.5	466.9	185.9	0.414	0.00	0	54	0.0
	5000	487.4	464.0	182.3	0.409	0.00	0	54	0.0
	5100	489.4	475.2	180.6	0.395	0.00	0	53	0.0
	5200	475.1	470.4	183.6	0.404	0.00	0	50	0.0
	5300	462.2	466.4	179.7	0.400	0.00	0	51	0.0
	5400	455.4	468.3	170.2	0.378	0.00	0	53	0.0
**	5500	452.0	473.4	183.9	0.404	0.00	0	53	0.0
	5600	437.0	465.9	187.2	0.419	0.00	0	53	0.0
	5700	422.0	458.0	191.4	0.436	0.00	0	53	0.0

**Range: 3600 RPM - 5500 RPM

AVG:	4550	513.9	442.6	165.5	0.389	0.00	0	54	0.0
MIN:	3600	452.0	335.6	130.7	0.350	0.00	0	50	0.0
MAX:	5500	553.2	475.2	188.8	0.416	0.00	0	56	0.0