

Listing of: TIP46313 (C:\WINDYN\901\DATA\TIP46313.SFD)  
 Channel Group: Corrected Torque and Power Page 1 of 1  
 Printed on Sep 5, 2007 at 17:31:57  
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Air1+2 scfm	AirTmp degF	VolEff %
**	4300	564.7	462.3	186.2	0.446	0.00	0	89	0.0
	4400	572.8	479.9	186.2	0.430	0.00	0	89	0.0
	4500	578.3	495.5	188.4	0.422	0.00	0	89	0.0
	4600	588.1	515.0	190.4	0.410	0.00	0	89	0.0
	4700	582.9	521.6	191.4	0.407	0.00	0	89	0.0
	4800	582.0	531.9	195.1	0.407	0.00	0	89	0.0
	4900	596.5	556.5	202.9	0.404	0.00	0	89	0.0
	5000	573.8	546.3	202.5	0.412	0.00	0	89	0.0
	5100	576.3	559.6	208.8	0.415	0.00	0	89	0.0
	5200	584.5	578.7	209.4	0.402	0.00	0	89	0.0
	5300	580.5	585.8	212.3	0.403	0.00	0	89	0.0
	5400	571.2	587.3	220.7	0.418	0.00	0	89	0.0
	5500	568.3	595.1	225.4	0.422	0.00	0	89	0.0
	5600	582.4	621.0	231.3	0.415	0.00	0	89	0.0
	5700	574.1	623.1	234.4	0.419	0.00	0	89	0.0
	5800	564.9	623.8	237.4	0.424	0.00	0	89	0.0
	5900	554.7	623.1	245.0	0.440	0.00	0	90	0.0
	6000	555.0	634.1	241.8	0.427	0.00	0	90	0.0
**	6100	548.0	636.4	253.9	0.447	0.00	0	90	0.0
	6200	545.0	643.4	255.8	0.445	0.00	0	90	0.0
	6300	542.2 **	650.4 **	253.7	0.437	0.00	0	90	0.0
	6400	527.7	643.0	251.4	0.439	0.00	0	90	0.0
	6500	501.3	620.4	258.8	0.468	0.00	0	88	0.0

\*\*Range: 4300 RPM - 6100 RPM  
 AVG: 5200 573.6 567.2 213.9 0.419 0.00 0 89 0.0  
 MIN: 4300 548.0 462.3 186.2 0.402 0.00 0 89 0.0  
 MAX: 6100 596.5 636.4 253.9 0.447 0.00 0 90 0.0