

Listing of: (memory data)
Channel Group: Corrected Torque and Power Page 1 of 1
Printed on Mar 4, 2006 at 12:24:15
Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Air1+2 scfm	AirTmp degF	VolEff %
	4100	630.3	492.0	196.5	0.408	0.00	0	46	0.0
	4200	637.9	510.1	197.4	0.395	0.00	0	46	0.0
	4300	643.3	526.7	204.3	0.395	0.00	0	44	0.0
	4400	652.5	546.7	225.2	0.420	0.00	0	45	0.0
**	4500	658.8	564.5	229.1	0.414	0.00	0	46	0.0
	4600	657.3	575.7	225.0	0.399	0.00	0	46	0.0
	4700	657.4	588.3	226.2	0.393	0.00	0	46	0.0
	4800	651.7	595.6	220.9	0.378	0.00	0	45	0.0
	4900	655.3	611.3	236.9	0.395	0.00	0	45	0.0
	5000	649.6	618.4	237.5	0.392	0.00	0	46	0.0
	5100	651.2	632.3	238.1	0.385	0.00	0	46	0.0
	5200	646.2	639.8	257.1	0.411	0.00	0	46	0.0
	5300	647.3	653.2	250.8	0.392	0.00	0	46	0.0
	5400	641.9	659.9	238.7	0.370	0.00	0	46	0.0
	5500	633.2	663.1	249.5	0.385	0.00	0	47	0.0
	5600	628.3	669.9	238.4	0.364	0.00	0	47	0.0
	5700	617.0	669.6	252.4	0.386	0.00	0	47	0.0
	5800	605.6	668.8	267.2	0.409	0.00	0	47	0.0
	5900	604.7	679.3	257.6	0.388	0.00	0	47	0.0
	6000	597.3	682.4	264.6	0.397	0.00	0	47	0.0
**	6100	589.4	684.5	272.5	0.408	0.00	0	47	0.0
	6200	576.5	680.6	264.3	0.398	0.00	0	47	0.0
	6300	565.2	678.0	267.9	0.405	0.00	0	47	0.0
**Range: 4500 RPM - 6100 RPM									
AVG:	5300	634.8	638.6	244.9	0.392	0.00	0	46	0.0
MIN:	4500	589.4	564.5	220.9	0.364	0.00	0	45	0.0
MAX:	6100	658.8	684.5	272.5	0.414	0.00	0	47	0.0