

Listing of: TIPHP11 (C:\WINDYN\901\DATA\TIPHP11.SFD)
Channel Group: Corrected Torque and Power Page 1 of 1
Printed on Jun 18, 2008 at 16:15:11
Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	FulA+B lb/hr	BSFC lb/hph	A/F Ratio	Airl+2 scfm	AirTmp degF	VolEff %
	3600	523.0	358.5	138.0	0.425	0.00	0	87	0.0
**	3700	522.1	367.8	136.8	0.411	0.00	0	87	0.0
	3800	537.1	388.6	141.2	0.402	0.00	0	87	0.0
	3900	537.9	399.4	139.2	0.386	0.00	0	88	0.0
	4000	544.9	415.0	145.7	0.389	0.00	0	88	0.0
	4100	552.0	431.0	149.5	0.384	0.00	0	88	0.0
	4200	574.5	459.4	150.8	0.363	0.00	0	88	0.0
	4300	583.7	477.9	156.2	0.362	0.00	0	88	0.0
	4400	591.3	495.4	165.3	0.369	0.00	0	88	0.0
	4500	588.8	504.5	165.1	0.362	0.00	0	87	0.0
	4600	588.5	515.4	173.8	0.373	0.00	0	88	0.0
	4700	591.9	529.7	172.4	0.361	0.00	0	89	0.0
	4800	590.6	539.7	182.0	0.374	0.00	0	89	0.0
	4900	584.0	544.9	183.9	0.375	0.00	0	89	0.0
	5000	581.0	553.1	182.2	0.366	0.00	0	88	0.0
	5100	579.0	562.3	188.0	0.371	0.00	0	88	0.0
	5200	577.7	571.9	193.2	0.375	0.00	0	88	0.0
	5300	575.3	580.6	198.9	0.381	0.00	0	88	0.0
**	5400	564.5	580.4	208.9	0.400	0.00	0	88	0.0
	5500	544.5	570.2	208.7	0.408	0.00	0	88	0.0
	5600	529.8	564.9	217.4	0.429	0.00	0	88	0.0
	5700	510.0	553.5	225.9	0.457	0.00	0	90	0.0
	5800	489.5	540.6	218.4	0.452	0.00	0	89	0.0
	5900	470.7	528.8	223.6	0.474	0.00	0	89	0.0
	6000	464.2	530.3	220.4	0.467	0.00	0	89	0.0
**Range: 3700 RPM - 5400 RPM									
AVG:	4550	570.3	495.4	168.5	0.378	0.00	0	88	0.0
MIN:	3700	522.1	367.8	136.8	0.361	0.00	0	87	0.0
MAX:	5400	591.9	580.6	208.9	0.411	0.00	0	89	0.0