

Listing of: CB39405 (C:\WINDYN\901\DATA\CB39405.SFD)
 Channel Group: Corrected Torque and Power Page 1 of 1
 Printed on Sep 12, 2016 at 12:01:38
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	Fuel B lb/hr	BSFC B lb/hph	A/F L1 Ratio	A/F L2 Ratio	AirTmp degF	WtrOut degF
**	3200	402.3	245.1	92.1	0.417	14.7	14.6	80	180
	3300	401.3	252.2	95.9	0.422	13.4	14.3	80	180
	3400	401.5	259.9	92.6	0.396	12.7	14.2	80	180
	3500	397.9	265.2	92.0	0.386	12.5	14.2	80	180
	3600	399.7	274.0	97.6	0.396	12.5	14.1	80	180
	3700	397.3	279.9	101.4	0.404	12.5	14.0	83	180
	3800	400.8	290.0	102.3	0.394	12.6	13.9	83	180
	3900	400.5	297.4	105.6	0.396	12.6	13.9	82	180
	4000	406.0	309.2	101.8	0.367	14.4	13.9	82	180
	4100	399.9	312.2	113.0	0.404	13.5	13.8	82	180
	4200	398.4	318.6	116.7	0.409	13.2	13.7	82	180
	4300	393.0	321.7	120.5	0.419	12.9	13.8	83	180
	4400	388.8	325.8	122.8	0.422	12.9	13.8	83	180
	4500	390.5	334.6	126.5	0.423	15.5	13.9	83	180
	4600	389.1	340.8	129.2	0.425	14.1	13.8	83	180
	4700	382.8	342.6	130.9	0.428	15.2	13.8	83	180
	4800	379.2	346.6	131.5	0.426	13.8	13.9	83	180
	4900	371.2	346.4	134.2	0.435	13.3	13.9	83	181
**	5000	365.8	348.3	132.6	0.427	12.9	13.8	81	181
	5100	352.1	341.9	143.4	0.470	12.7	13.8	80	181

**Range: 3200 RPM - 5000 RPM
 AVG: 4100 393.0 305.8 112.6 0.410 13.4 14.0 82 180
 MIN: 3200 365.8 245.1 92.0 0.367 12.5 13.7 80 180
 MAX: 5000 406.0 348.3 134.2 0.435 15.5 14.6 83 181