

Listing of: (memory data)
 Channel Group: Corrected Torque and Power Page 1 of 1
 Printed on Jul 16, 2019 at 16:45:28
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	Fuel B lb/hr	BSFC B lb/hph	A/F_L1 Ratio	A/F_L2 Ratio	AirTmp degF	WtrOut degF
	4000	550.1	418.9	167.3	0.449	14.6	10.0	88	177
**	4100	556.2	434.2	166.1	0.430	15.4	10.0	88	177
	4200	564.5	451.4	170.6	0.425	15.9	10.0	88	177
	4300	573.6	469.6	168.6	0.404	15.0	10.0	88	177
	4400	576.7	483.1	172.9	0.403	14.3	10.0	88	176
	4500	575.9	493.4	179.4	0.409	13.8	10.0	88	176
	4600	590.1	516.8	179.7	0.391	14.5	10.0	88	176
	4700	593.5	531.1	185.7	0.394	16.1	10.0	88	176
	4800	582.9	532.7	192.6	0.407	14.8	10.0	88	176
	4900	579.3	540.5	200.7	0.419	13.7	10.0	88	176
**	5000	584.4	556.3	205.8	0.417	14.4	10.0	88	178
	5100	587.3	570.3	215.4	0.426	13.6	10.0	88	178
	5200	583.9	578.1	212.6	0.415	14.6	10.0	88	178
	5300	575.0	580.3	219.9	0.428	13.4	10.0	88	178
	5400	574.2	590.4	219.9	0.421	14.6	10.0	88	178
	5500	571.3	598.3	221.0	0.418	14.3	10.0	88	178
	5600	556.5	593.4	232.6	0.444	15.2	10.0	88	178
	5700	554.1	601.4	239.5	0.451	14.0	10.0	88	178
	5800	541.6	598.1	231.4	0.439	15.1	10.0	88	178
	5900	542.0	608.9	241.1	0.450	15.1	10.0	88	179
	6000	526.8	601.8	243.4	0.460	15.0	10.0	88	179
**Range: 4100 RPM - 5000 RPM									
AVG:	4550	577.7	500.9	182.2	0.410	14.8	10.0	88	176
MIN:	4100	556.2	434.2	166.1	0.391	13.7	10.0	88	176
MAX:	5000	593.5	556.3	205.8	0.430	16.1	10.0	88	178