

Listing of: TIP46405 (C:\WINDYN\901\DATA\TIP46405.SFD)
 Channel Group: Corrected Torque and Power Page 1 of 1
 Printed on Jun 23, 2023 at 14:47:33
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	Fuel B lb/hr	BSFC B lb/hph	A/F_L1 Ratio	A/F_L2 Ratio	AirTmp degF	WtrOut degF
**	3800	577.3	417.7	174.2	0.454	14.0	10.0	76	178
	3900	583.4	433.2	173.7	0.437	16.1	10.0	77	178
	4000	584.9	445.5	183.8	0.449	16.1	10.0	76	178
	4100	589.8	460.4	181.6	0.430	15.7	10.0	76	178
	4200	605.6	484.3	188.3	0.423	14.7	10.0	75	178
	4300	610.5	499.8	194.3	0.423	14.3	10.0	75	178
	4400	611.7	512.4	202.1	0.429	13.9	10.0	75	178
	4500	617.5	529.1	204.7	0.421	14.8	10.0	75	178
	4600	621.3	544.2	199.7	0.399	14.2	10.0	75	178
	4700	618.9	553.8	202.2	0.397	13.7	10.0	75	179
	4800	612.9	560.2	205.1	0.399	13.4	10.0	76	179
	4900	622.8	581.1	208.3	0.390	14.9	10.0	75	177
	5000	611.6	582.3	216.4	0.405	15.8	10.0	76	178
	5100	606.0	588.5	225.3	0.418	16.1	10.0	76	178
	5200	604.2	598.2	243.0	0.444	14.7	10.0	76	178
	5300	600.7	606.2	246.4	0.444	15.2	10.0	76	178
	5400	592.5	609.2	265.1	0.476	14.2	10.0	76	179
	5500	588.0	615.8	253.8	0.451	14.1	10.0	76	179
	5600	575.4	613.5	245.8	0.437	14.0	10.0	74	179
	5700	571.1	619.8	254.8	0.449	14.7	10.0	74	179
	5800	556.5	614.6	254.5	0.454	15.1	10.0	76	177
**	5900	551.3	619.3	259.9	0.460	15.3	10.0	76	178
	6000	544.7	622.3	256.6	0.453	16.2	10.0	76	179

**Range: 3800 RPM - 5900 RPM
 AVG: 4850 596.1 549.5 217.4 0.431 14.8 10.0 76 178
 MIN: 3800 551.3 417.7 173.7 0.390 13.4 10.0 74 177
 MAX: 5900 622.8 619.8 265.1 0.476 16.1 10.0 77 179