

Listing of: TIP46408 (C:\WINDYN\901\DATA\TIP46408.SFD)  
 Channel Group: Corrected Torque and Power Page 1 of 1  
 Printed on Jun 23, 2023 at 14:43:54  
 Test Description: Accel. Test - 300 rpm/second

	EngSpd RPM	STPTrq Clb-ft	STPPwr CHp	Fuel B lb/hr	BSFC B lb/hph	A/F_L1 Ratio	A/F_L2 Ratio	AirTmp degF	WtrOut degF
**	3900	559.0	415.1	174.7	0.464	12.8	10.0	79	180
	4000	563.4	429.1	199.2	0.512	12.8	10.0	79	180
	4100	566.8	442.4	167.1	0.417	13.4	10.0	79	180
	4200	579.1	463.1	172.8	0.412	13.3	10.0	79	181
	4300	582.0	476.5	184.7	0.428	13.3	10.0	79	181
	4400	587.9	492.5	182.0	0.408	14.9	10.0	79	181
	4500	597.6	512.0	192.5	0.415	14.4	10.0	79	181
	4600	594.6	520.8	199.5	0.423	14.8	10.0	79	181
	4700	597.6	534.8	210.7	0.435	14.9	10.0	80	181
	4800	606.3	554.1	211.7	0.422	13.7	10.0	80	181
	4900	599.5	559.3	222.8	0.441	15.0	10.0	80	181
	5000	596.5	567.9	221.9	0.432	15.4	10.0	80	181
	5100	598.0	580.7	225.2	0.430	14.4	10.0	81	181
	5200	595.4	589.5	235.3	0.442	13.6	10.0	80	181
	5300	590.3	595.7	231.4	0.430	13.4	10.0	80	181
	5400	581.6	597.9	238.6	0.442	14.3	10.0	80	181
	5500	573.9	601.0	245.0	0.452	13.5	10.0	80	181
	5600	570.4	608.2	239.8	0.438	13.3	10.0	80	181
	5700	563.5	611.6	249.9	0.453	14.8	10.0	78	181
	5800	559.1	617.4	254.6	0.457	15.2	10.0	78	178
	5900	547.8	615.4	253.8	0.458	15.6	10.0	78	179
**	6000	542.3	619.5	259.7	0.466	15.8	10.0	78	180
**Range: 3900 RPM - 6000 RPM									
AVG:	4950	579.7	545.7	216.9	0.440	14.2	10.0	79	181
MIN:	3900	542.3	415.1	167.1	0.408	12.8	10.0	78	178
MAX:	6000	606.3	619.5	259.7	0.512	15.8	10.0	81	181